

View Online at https://aerobasegroup.com/nsn/5910-01-257-2965

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

### **Body Diameter:**

0.225 inches

**Body Length:** 

0.762 inches

**Terminal Diameter:** 

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

33.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1500

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# **Specification Data:**

81349-mil-c-20/5 government specification

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0