NSN 5910-01-257-3014

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-257-3014

Body Style:

W/thd mtg studs, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

Between 0.557 inches and 0.577 inches

Body Length:

1.406 inches

Terminal Diameter:

0.032 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.750 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

21.0 megohms

Capacitance Value Per Section:

0.390 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Thread Tolerance Class:

2a external

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.100

NSN 5910-01-257-3014

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig: A010b0