

View Online at <https://aerobasegroup.com/nsn/5910-01-257-9578>

Body Style:

Dual inline

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Terminal Length:

Between 0.120 inches and 0.176 inches

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 0.387 inches and 0.395 inches

Body Width:

Between 0.290 inches and 0.315 inches

Body Height:

0.175 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.300 inches and 0.400 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Section Quantity:

4

Capacitance Value Per Section:

51.000 picofarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 all sections

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc all sections

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 all sections

Tolerance Range Per Section:

-5.00/+5.00 percent all sections

Case Material:

Plastic or ceramic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.100

Quality Factor At Reference Temp:

1000.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0