NSN 5910-01-257-9761

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-257-9761 **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Terminal Length:** 1.500 inches **Body Diameter:** 0.135 inches **Body Length:** 0.422 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Capacitance Value Per Section:** 3.900 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Case Insulation Material: Plastic Test Data Document:** 81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-39003/01 government specification Shelf Life: N/a **Unit Of Measure:**

Fiig: A010b0

No

Demilitarization: