NSN 5910-01-258-3349

Specification Data:

81349-mil-c-49137/5 government specification

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-258-3349

| Body Style: |
|--|
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.000 inches |
| Body Diameter: |
| 0.170 inches |
| Body Length: |
| 0.410 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Solid |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 4.700 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Capacitive Electrode Material: |
| Tantalum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 6.0000 |
| Dc Leakage At Reference Temp: |
| 3.000 microamperes |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-49137 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |

NSN 5910-01-258-3349

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0