

NSN 5910-01-258-7978 Plastic Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-258-7978 **Body Style:** Rotary **Terminal Length:** 0.158 inches **Body Length:** 0.400 inches **Body Width:** 0.350 inches **Body Height:** 0.354 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.350 inches **Terminal Diameter:** 0.032 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 0.350 inches **Quality Factor At 25 Deg Celsius:** 1000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.327 inches **Inclosure Type: Encased Terminal Location:** End opposite adjustment control perpendicular **Adjustment Device Rotation:**

180.0 degrees clockwise

Adjustment Device Torque:

Between 0.150 inch-ounces and 4.900 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

4 terminal

Nonderated Operating Temp:

Between -40.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+7.0/+100.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Material:

Plastic polysulfone base

NSN 5910-01-258-7978

Plastic Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
4 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0