NSN 5910-01-259-0890



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-259-0890 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.250 inches **Body Length:** 0.630 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **End Application:** 6625-01-018-1084 multimeter **Capacitance Value Per Section:** 68.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 13.000 Dc Leakage At Reference Temp: 0.400 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-259-0890

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0