## NSN 5910-01-259-1971

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-259-1971						
Body Style:						
W/o mtg facilities, terminal (s) on one surface						
Reliability Indicator:						
Not established						
Terminal Length:						
Between 0.313 inches and 0.687 inches						
Body Length:						
3.750 inches						
Body Width:						
3.188 inches						
Body Height:						
4.750 inches						
Center To Center Distance Between Terminals Parallel To Length:						
2.062 inches						
Terminal Diameter:						
0.190 inches						
Schematic Diagram Designator:						
No common or grounded electrode (s)						
Mounting Facility Screw Thread Series Designator:						
Unf						
Mounting Facility Type And Quantity:						
2 threaded mounting studs						
Capacitance Value Per Section:						
2.500 microfarads single section						
Nonderated Operating Temp:						
Between -55.0 degrees celsius and 85.0 degrees celsius						
Thread Size:						
0.190 inches						
Nonderated Continuous Voltage Rating And Type Per Section:						
660.0 ac-rms single section and 1000.0 dc single section						
Tolerance Range Per Section:						
-6.00 to 6.00 percent single section						
Case Material:						
Metal						
Insulation Resistance At Reference Temp:						
10000.0 megohms						
Terminal Surface Treatment:						
Solder						
Terminal Type And Quantity:						
2 threaded stud						

N/a

Shelf Life:

## NSN 5910-01-259-1971

Paper Dielectric Fixed Capacitor - Page 2 of 2



	• •			
 n	1+	<i>(</i> )+	Meas	uro.

--

Demilitarization:

No

Fiig:

A010b0