## NSN 5910-01-259-1971

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-259-1971
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.313 inches and 0.687 inches
Body Length:
3.750 inches
Body Width:
3.188 inches
Body Height:
4.750 inches
Center To Center Distance Between Terminals Parallel To Length:
2.062 inches
Terminal Diameter:
0.190 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unf
Mounting Facility Type And Quantity:
2 threaded mounting studs
Capacitance Value Per Section:
2.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.190 inches
Nonderated Continuous Voltage Rating And Type Per Section:
660.0 ac-rms single section and 1000.0 dc single section
Tolerance Range Per Section:
-6.00 to 6.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
10000.0 megohms
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 threaded stud

N/a

Shelf Life:

## NSN 5910-01-259-1971

Paper Dielectric Fixed Capacitor - Page 2 of 2



	• •					
ın	18	<i>(</i> )+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A010b0