## NSN 5910-01-259-3579

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-259-3579

| Body Style:  |
|--|
| W/o mtg facilities, axial terminals                        |
| Reliability Indicator:                                     |
| Not established  |
| Terminal Length:   |
| 1.625 inches   |
| Body Diameter:   |
| 0.190 inches   |
| Body Length:   |
| 0.560 inches   |
| Terminal Diameter:   |
| 0.020 inches   |
| Schematic Diagram Designator:                              |
| No common or grounded electrode (s)                        |
| Insulation Resistance At Maximum Operating Temp:           |
| 500.0 megohms  |
| Capacitance Value Per Section:                             |
| 0.120 microfarads single section                           |
| Nonderated Operating Temp:                                 |
| Between -55.0 degrees celsius and 125.0 degrees celsius    |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section                                    |
| Tolerance Range Per Section:                               |
| -5.00/+5.00 percent single section                         |
| Case Material:   |
| Plastic  |
| Insulation Resistance At Reference Temp:                   |
| 100000.0 megohms   |
| Dissipation Factor At Reference Tempurature In Percent:    |
| 0.250  |
| Terminal Surface Treatment:                                |
| Solder   |
| Terminal Type And Quantity:                                |
| 2 uninsulated wire lead                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| _  |
| Demilitarization:  |
| No   |

Fiig:

A010b0