NSN 5910-01-259-5460

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-259-5460

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.505 inches
Body Width:
0.414 inches
Body Height:
0.188 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.022 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
160.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohm-microfarads
100000.0 megohm-microfarads Power Factor At Reference Tempurature In Percent:
•
Power Factor At Reference Tempurature In Percent:
Power Factor At Reference Tempurature In Percent: 0.300
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment:
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment: Solder
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Power Factor At Reference Tempurature In Percent: 0.300 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

NSN 5910-01-259-5460

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0