## NSN 5910-01-259-6352

**Body Style:** 

N/a

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-259-6352

W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Length:
0.420 inches
Body Width:
0.300 inches
Body Height:
0.180 inches
Center To Center Distance Between Terminals Parallel To Length:
0.300 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
4935-01-207-5355 test station, gu
Insulation Resistance At Maximum Operating Temp:
50.0 megohm-microfarads
Capacitance Value Per Section:
0.150 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
25000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

## NSN 5910-01-259-6352

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -					
ш	ın	18 1	r 1+	Me	20	ıır	Δ.
u	,,,	IL	v.	IAIC	as	uı	┖.

--

Demilitarization:

No

Fiig:

A010b0