NSN 5910-01-260-1360

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-260-1360

Body Style: W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.250 inches **Body Diameter:** 1.385 inches **Body Length:** 3.140 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.500 inches **Terminal Diameter:** 0.313 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 2 threaded mounting holes **Capacitance Value Per Section:** 23000.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Thread Size: 0.190 inches Dc Leakage At Maximum Operating Temp: 6000.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.043

NSN 5910-01-260-1360

Electrolytic Fixed Capacitor - Page 2 of 2



| Dc Leakage At Reference Temp: |
|-------------------------------|
| 100.000 microamperes |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 threaded hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A010b0