NSN 5910-01-260-3786

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-260-3786

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.032 inches and 0.094 inches

Body Diameter:

Between 1.354 inches and 1.430 inches

Body Length:

Between 2.078 inches and 2.217 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.484 inches and 0.516 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Unf

Mounting Facility Screw Thread Series Designator:

Mounting Facility Type And Quantity:

2 threaded mounting holes

Capacitance Value Per Section:

1800.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Thread Size:

0.190 inches

Dc Leakage At Maximum Operating Temp:

2.8 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.048

NSN 5910-01-260-3786

Electrolytic Fixed Capacitor - Page 2 of 2



Dc Leakage At Reference Temp:
0.460 milliamperes
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0