Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-261-2182

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.500 inches

**Body Length:** 

1.125 inches

### **Body Width:**

0.765 inches

**Body Height:** 

### 0.590 inches

### Center To Center Distance Between Terminals Parallel To Length:

Between 0.843 inches and 0.907 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

200.0 megohm-microfarads

### **Capacitance Value Per Section:**

0.220 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

360.0 ac-rms single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

0.800

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No



**Fiig:** A010b0