Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-261-2211

## **Body Style:**

W/o mtg facilities, terminal (s) on one end

# **Reliability Indicator:**

Not established

# **Terminal Length:**

0.250 inches

### **Body Diameter:**

2.000 inches

#### **Body Length:**

3.125 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

0.875 inches

### **Terminal Diameter:**

0.190 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Anode Type:

Plain foil

# Electrical Polarization:

Polarized

# **End Application:**

6350-01-234-6555 muffler

## Mounting Facility Screw Thread Series Designator:

Unf

## Mounting Facility Type And Quantity:

2 threaded mounting holes

## Capacitance Value Per Section:

4100.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

#### **Thread Size:**

0.190 inches

#### Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+75.00 percent single section

#### Case Material:

Metal

### **Capacitive Electrode Material:**

Aluminum

#### Equivalent Series Resistance At Reference Tempurature In Ohms:

0.018

Electrolytic Fixed Capacitor - Page 2 of 2



Dc Leakage At Reference Temp:

550.000 milliamperes

**Case Insulation Material:** 

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0