

View Online at https://aerobasegroup.com/nsn/5910-01-261-8299

### **Body Style:**

W/o mtg facilities, radial terminals

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

### **Body Diameter:**

0.350 inches

### **Body Length:**

0.120 inches

### Center To Center Distance Between Terminals Parallel To Diameter:

0.250 inches

### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

# Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

### Capacitance Value Per Section:

27.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-60.0/+60.0 single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

50000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1500

### **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead



**Specification Data:** 

81349-mil-c-20/17 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0