## NSN 5910-01-261-9533

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-261-9533 **Body Style:** W/mtg tabs/flanges terminals on opposite surfaces **Reliability Indicator:** Not established **Terminal Length:** 0.750 inches **Body Length:** 2.000 inches **Body Width:** 2.000 inches **Body Height:** Between 1.063 inches and 1.250 inches Center To Center Distance Between Terminals Parallel To Length: 1.062 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1500.0 megohms **Capacitance Value Per Section:** 8.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 4500.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 solder stud

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

## NSN 5910-01-261-9533

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0