NSN 5910-01-262-0870

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-262-0870

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.625 inches
Body Diameter:
1.000 inches
Body Length:
1.875 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
25000.0 megohms
Capacitance Value Per Section:
20.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
250000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.250
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-262-0870

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Specification Data:
81349-mil-c-39022/10 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0