NSN 5910-01-262-1706

Body Style:

N/a

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-262-1706

W/thd bushing mtg, terminal (s) on one end					
Reliability Indicator:					
Not established					
Body Diameter:					
0.670 inches					
Body Length:					
1.875 inches					
Center To Center Distance Between Terminals Parallel To Diameter:					
0.218 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Mounting Facility Screw Thread Series Designator:					
Unf					
Mounting Facility Type And Quantity:					
1 threaded bushing					
Features Provided:					
Hermetically sealed case					
Insulation Resistance At Maximum Operating Temp:					
500.0 megohm-microfarads					
Capacitance Value Per Section:					
6.800 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 105.0 degrees celsius					
Thread Size:					
0.500 inches					
Nonderated Continuous Voltage Rating And Type Per Section:					
100.0 dc single section					
Tolerance Range Per Section:					
-5.00/+5.00 percent single section					
Case Material:					
Metal					
Insulation Resistance At Reference Temp:					
50000.0 megohm-microfarads					
Dissipation Factor At Reference Tempurature In Percent:					
1.000					
Terminal Surface Treatment:					
Solder					
Terminal Type And Quantity:					
2 tab, solder lug					
Shelf Life:					

NSN 5910-01-262-1706

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A010b0