## NSN 5910-01-262-2483



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-262-2483 **Body Style:** W/o mtg facilities, radial terminals Reliability Indicator: Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.200 inches **Body Length:** 0.400 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.250 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 6625-01-188-7441 generator, signa **Capacitance Value Per Section:** 7.000 picofarads single section **Nonderated Operating Temp:** 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -60.0/+60.0 single section **Tolerance Range Per Section:** -0.10/+0.10 picofarads single section Case Material: Ceramic **Insulation Resistance At Reference Temp:** 50000.0 megohms **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-01-262-2483

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0