## NSN 5910-01-263-1890

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-263-1890 **Body Style:** Rotary **Terminal Length:** 0.131 inches **Overall Height:** 0.200 inches **Overall Diameter:** Between 0.195 inches and 0.226 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+400.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.198 inches **Quality Factor At 25 Deg Celsius:** 500.0 **End Application:** 5895-01-195-0827 receiver-transm **Inclosure Type: Encased Adjustment Device Torque:** 0.200 inch-ounces and 2.800 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 unthreaded hole **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +7.0/+50.0 single section **Nonderated Voltage Rating And Type:** 100.0 ac continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Capacitance Drift In Picofarads:** 1.50 single section **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5910-01-263-1890

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0