## NSN 5910-01-263-2637

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-263-2637

Body	Stv	le٠
Bouv	JLV	ıc.

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

**Body Length:** 

Between 0.500 inches and 0.626 inches

**Body Width:** 

Between 0.179 inches and 0.241 inches

**Body Height:** 

Between 0.297 inches and 0.359 inches

**Terminal Diameter:** 

0.020 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

3000.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.100 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

30000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.500

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polyethylene terephthalate

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-263-2637

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0