NSN 5910-01-264-1812

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-264-1812

| view Offiline at https://acrobasegroup.com/histi/5910-01-204-1012 |
|---|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 40.0 millimeters |
| Body Diameter: |
| 6.0 millimeters |
| Body Length: |
| 14.0 millimeters |
| Terminal Diameter: |
| 0.7 millimeters |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| 6130-01-101-0512 power supply |
| Capacitance Value Per Section: |
| 0.068 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 100.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 250.0 dc single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 30000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.100 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A010b0