NSN 5910-01-264-2817

W/thd mtg bushing, terminals on opposite ends

Body Style:

Reliability Indicator:

Not established

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-264-2817

Width Across Flats:
0.187 inches
Terminal Length:
1.000 inches
Body Length:
0.500 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Mounting English Type And Quantity
Mounting Facility Type And Quantity:
1 threaded bushing
1 threaded bushing
1 threaded bushing Insulation Resistance At Maximum Operating Temp:
1 threaded bushing Insulation Resistance At Maximum Operating Temp: 1000.0 megohms
1 threaded bushing Insulation Resistance At Maximum Operating Temp: 1000.0 megohms Capacitance Value Per Section:
1 threaded bushing Insulation Resistance At Maximum Operating Temp: 1000.0 megohms Capacitance Value Per Section: 0.100 microfarads single section
1 threaded bushing Insulation Resistance At Maximum Operating Temp: 1000.0 megohms Capacitance Value Per Section: 0.100 microfarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change:

50.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Thread Size: 0.138 inches

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

Nonderated Continuous Voltage Rating And Type Per Section:

2.500

Terminal Surface Treatment:

Solder

Precious Material And Location:

Case surfaces gold

NSN 5910-01-264-2817

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0