NSN 5910-01-264-3214

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-264-3214

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Body Length:
0.260 inches
Body Width:
0.092 inches
Body Height:
0.128 inches
Center To Center Distance Between Terminals Parallel To Length:
0.325 inches
Terminal Diameter:
0.019 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
3.300 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-60.0/+60.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-0.50/+0.50 percent single section
Case Material:
Plastic
Test Data Document:
81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-c-39014/22 government specification
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5910-01-264-3214

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0