

View Online at https://aerobasegroup.com/nsn/5910-01-264-3218

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Established

## **Reliability Failure Rate Level In Percent:**

1.000

## Body Length:

0.260 inches

#### **Body Width:**

0.092 inches

#### **Body Height:**

0.128 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.325 inches

#### **Terminal Diameter:**

0.019 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## **Capacitance Value Per Section:**

12.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-60.0/+60.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-0.50/+0.50 percent single section

#### **Case Material:**

Plastic

#### **Test Data Document:**

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-39014/22 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5910-01-264-3218 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

