

View Online at <https://aerobasegroup.com/nsn/5910-01-264-3219>

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Body Length:

0.260 inches

Body Width:

0.092 inches

Body Height:

0.128 inches

Center To Center Distance Between Terminals Parallel To Length:

0.325 inches

Terminal Diameter:

0.019 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

27.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-30.0/+30.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Test Data Document:

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39014/22 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0