

View Online at https://aerobasegroup.com/nsn/5910-01-265-3082

Body Style:	
Cylindrical	
Overall Length:	
0.490 inches	
Terminal Length:	
0.125 inches	
Overall Diameter:	
0.312 inches	
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:	
0.0 single section	
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:	
-150.0/+150.0 single section	
Center To Center Distance Between Terminals Parallel To Height:	
0.280 inches	
Terminal Diameter:	
0.040 inches	
Quality Factor At 25 Deg Celsius:	
800.0	
Inclosure Type:	
Encapsulated	
Terminal Location:	
Circumference on end opposite adjustment control bent backward	
Adjustment Device Torque:	
Between 0.500 inch-ounces and 5.000 inch-ounces	
Insulation Dc Resistance At 25 Deg Celsius:	
1000000.0 megohms	
Insulation Dc Resistance At Max Operating Temp:	
100000.0 megohms	
Mounting Facility Type And Quantity:	
2 terminal	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Capacitance Range In Picofarads:	
+1.5/+30.0 single section	
Nonderated Voltage Rating And Type:	
250.0 dc continuous single section	
Adjustment Device Drive Type And Quantity:	
1 slotted screw	
Test Data Document:	
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification	on type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting generation	al type data on certain

Terminal Type And Quantity:

1 pin and 1 printed circuit



Specification Data:

81349-mil-c-14409/17 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0