

View Online at https://aerobasegroup.com/nsn/5910-01-265-7569

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.0100

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.670 inches

**Body Length:** 

1.374 inches

**Terminal Diameter:** 

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

25000.0 megohms

#### Capacitance Value Per Section:

5.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

250000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.2500

## **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

## **Test Data Document:**

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead



## **Specification Data:**

81349-mil-c-39022/10 government specification

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0