

View Online at https://aerobasegroup.com/nsn/5910-01-265-7594

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.190 inches

**Body Length:** 

0.530 inches

Terminal Diameter:

Between 0.019 inches and 0.024 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

7000.0 megohms

### **Capacitance Value Per Section:**

0.150 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.3000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-55514/4 government specification

Shelf Life:



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0