

View Online at https://aerobasegroup.com/nsn/5910-01-266-5371

| Body Style: | |
|--|-------|
| Chip type | |
| Reliability Indicator: | |
| Not established | |
| Body Length: | |
| Between 0.100 inches and 0.130 inches | |
| Body Width: | |
| Between 0.100 inches and 0.130 inches | |
| Body Height: | |
| 0.105 inches | |
| Schematic Diagram Designator: | |
| No common or grounded electrode (s) | |
| Features Provided: | |
| Hermetically sealed case | |
| Capacitance Value Per Section: | |
| 0.600 picofarads single section | |
| Nonderated Operating Temp: | |
| 125.0 degrees celsius | |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Cels | sius: |
| 90.0 single section | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 500.0 dc single section | |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsiu | ıs: |
| 20.0/+20.0 single section | |
| Tolerance Range Per Section: | |
| 0.10/+0.10 picofarads single section | |
| Terminal Type And Quantity: | |
| 2 bonding pad | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Filg: | |
| A010b0 | |