NSN 5910-01-266-7804

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-266-7804 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 20.0 millimeters **Body Diameter:** 8.7 millimeters **Body Length:** 12.5 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 5.0 millimeters **Terminal Diameter:** 0.8 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Polarized **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 6.3 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section Case Material: **Plastic Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 0.250 **Equivalent Series Resistance At Reference Tempurature In Ohms:** 1.81 **Terminal Surface Treatment:**

Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-01-266-7804

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0