NSN 5910-01-267-5329

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-267-5329 |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.120 inches |
| Body Length: |
| 0.310 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.175 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| Between 0.290 inches and 0.360 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 100.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 1000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.150 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 printed circuit |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5910-01-267-5329

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0