Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-267-9296

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

### **Terminal Length:**

1.500 inches

### **Body Diameter:**

0.351 inches

**Body Length:** 

0.786 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

## Capacitance Value Per Section:

220.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

# Tolerance Range Per Section:

-20.00/+20.00 percent single section

# **Capacitive Electrode Material:**

Tantalum

# **Test Data Document:**

81349-mil-r-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

### Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0