

View Online at <https://aerobasegroup.com/nsn/5910-01-269-5139>

Body Style:

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

0.500 inches

Body Length:

0.135 inches

Body Width:

Between 0.030 inches and 0.100 inches

Body Height:

0.110 inches

Center To Center Distance Between Terminals Parallel To Length:

0.119 inches

Terminal Diameter:

0.016 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

100000.0 megohms

Capacitance Value Per Section:

11.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

90.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Ceramic or glass

Insulation Resistance At Reference Temp:

1000000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.050

Quality Factor At Reference Temp:

10.000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-55681/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0