## NSN 5910-01-269-5143

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-269-5143

| view Online at https://aerobasegroup.com/nsn/5910-01-269-5143         |  |  |  |
|---|--|--|--|
| Body Style:   |  |  |  |
| W/o mtg facilities terminal (s) on one surface                        |  |  |  |
| Reliability Indicator:  |  |  |  |
| Not established   |  |  |  |
| Terminal Length:  |  |  |  |
| 1.250 inches  |  |  |  |
| Body Length:  |  |  |  |
| 0.800 inches  |  |  |  |
| Body Width:   |  |  |  |
| 0.750 inches  |  |  |  |
| Body Height:  |  |  |  |
| 0.250 inches  |  |  |  |
| Center To Center Distance Between Terminals Parallel To Length:       |  |  |  |
| 0.680 inches  |  |  |  |
| Terminal Diameter:  |  |  |  |
| 0.031 inches  |  |  |  |
| Schematic Diagram Designator:   |  |  |  |
| No common or grounded electrode (s)                                   |  |  |  |
| End Application:  |  |  |  |
| 1260-01-208-6448 mast mounted si                                      |  |  |  |
| Features Provided:  |  |  |  |
| Burn in   |  |  |  |
| Capacitance Value Per Section:  |  |  |  |
| 0.390 microfarads single section                                      |  |  |  |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |  |  |  |
| -15.0/+15.0 without voltage applied single section                    |  |  |  |
| Nonderated Operating Temp:  |  |  |  |
| Between -55.0 degrees celsius and 125.0 degrees celsius               |  |  |  |
| Nonderated Continuous Voltage Rating And Type Per Section:            |  |  |  |
| 1000.0 dc single section  |  |  |  |
| Tolerance Range Per Section:  |  |  |  |
| -20.00/+20.00 percent single section                                  |  |  |  |
| Case Material:  |  |  |  |
| Ceramic   |  |  |  |
| Insulation Resistance At Reference Temp:                              |  |  |  |
| 1000.0 megohm-microfarads   |  |  |  |
| Dissipation Factor At Reference Tempurature In Percent:               |  |  |  |
| 2.500   |  |  |  |
| Terminal Surface Treatment:   |  |  |  |

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-269-5143

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0