

View Online at https://aerobasegroup.com/nsn/5910-01-269-5884

### **Body Style:**

W/o mtg facilities, radial terminals

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.225 inches

#### **Body Length:**

0.430 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.290 inches

#### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

5.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

# Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

# **Tolerance Range Per Section:**

-0.50/+0.50 percent single section

# **Test Data Document:**

81349-mil-g-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-g-20/3 government specification

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A010b0

# Mil-std (military Standard):

Mil-c-20 spec.