## NSN 5910-01-271-9890



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-271-9890 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.984 inches **Body Diameter:** 0.866 inches **Body Length:** 1.614 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.394 inches **Terminal Diameter:** 0.039 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 2.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 3300.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 22.000 Dc Leakage At Reference Temp: 0.030 microamperes **Terminal Surface Treatment:** Solder

**Case Insulation Material:**Plastic

## NSN 5910-01-271-9890

Electrolytic Fixed Capacitor - Page 2 of 2



Ferminal Type And Quai	ntity	:
------------------------	-------	---

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0