## NSN 5910-01-271-9891



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-271-9891 **Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Body Diameter:** 0.250 inches **Body Length:** 0.500 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.125 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **End Application:** 6625-01-126-7144 generator, time **Capacitance Value Per Section:** 22.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.000 Dc Leakage At Reference Temp: 5.000 microamperes **Terminal Surface Treatment:** Solder

**Case Insulation Material: Plastic** 

## NSN 5910-01-271-9891

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal <sup>-</sup>	Type	And	Quantity	<b>/</b> :
-----------------------	------	-----	----------	------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0