NSN 5910-01-272-5057

Quartz Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-272-5057 **Thread Class:** 2a **Body Style:** Piston **Terminal Length:** 1.500 inches **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.250 inches **Body Length:** 1.219 inches **Overall Diameter:** 0.313 inches **Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:** 25.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -25.0/+25.0 single section **Terminal Diameter:** 0.025 inches **Quality Factor At 25 Deg Celsius:** 1500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Terminal Location:** One side bent backward **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Bushing Width:** Between 0.230 inches and 0.234 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between 25.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches

Capacitance Range In Picofarads:

+0.6/+5.5 single section

NSN 5910-01-272-5057

Quartz Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Ra	ting And	Type:
-----------------------	----------	-------

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

1 tab, solder lug and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0