Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-272-5811

## **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Established

## **Reliability Failure Rate Level In Percent:**

0.001

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.135 inches

#### **Body Length:**

0.286 inches

#### **Terminal Diameter:**

0.020 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

0.047 microfarads single section

## Nonderated Operating Temp:

125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### Case Material:

Metal

**Capacitive Electrode Material:** 

Tantalum

#### **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-39003 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-39003/01 government specification

# Shelf Life:

N/a

Unit Of Measure:

Electrolytic Fixed Capacitor - Page 2 of 2

Demilitarization:

No

Fiig:

A010b0

