NSN 5910-01-274-0974

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-274-0974

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.0010
Terminal Length:
1.625 inches
Body Diameter:
0.342 inches
Body Length:
0.687 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
300000.0 megohms
Capacitance Value Per Section:
0.270 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
3000000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.1500
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-274-0974

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Specification Data:
81349-mil-c-83421/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A010b0