## NSN 5910-01-275-0740

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-275-0740

Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Diameter:
0.145 inches
Body Length:
0.600 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Solid
Impedance At Minimum Operating Tempurature In Ohms:
180.0
Electrical Polarization:
Polarized
End Application:
Measuring set, radio interference an/urm-200
Capacitance Value Per Section:
22.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
7.5 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
60.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
18.000
Dc Leakage At Reference Temp:
1.500 microamperes
Terminal Surface Treatment:

Solder

## NSN 5910-01-275-0740

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0