## NSN 5910-01-275-6520

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-275-6520

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.157 inches and 0.236 inches
Body Length:
1.020 inches
Body Width:
0.728 inches
Body Height:
0.256 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.888 inches and 0.912 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.200 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 100.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-
Tolerance Range Per Section:
Tolerance Range Per Section: -5.00/+5.00 percent single section
Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.500
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.500  Terminal Surface Treatment:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.500  Terminal Surface Treatment: Solder
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.500  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 30000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 1.500  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a

No

## NSN 5910-01-275-6520

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0