

View Online at <https://aerobasegroup.com/nsn/5910-01-275-7258>

**Body Style:**

W/o mtg facilities, terminals on opposite surfaces

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Terminal Length:**

1.000 inches

**Body Length:**

Between 0.379 inches and 0.434 inches

**Body Width:**

Between 0.040 inches and 0.140 inches

**Body Height:**

Between 0.130 inches and 0.230 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.410 inches and 0.470 inches

**Terminal Diameter:**

Between 0.015 inches and 0.020 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**End Application:**

5895-01-205-6148 receiver-excite

**Insulation Resistance At Maximum Operating Temp:**

7000.0 megohms

**Capacitance Value Per Section:**

0.018 microfarads single section

**Nonderated Operating Temp:**

125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

500000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.300

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-55514/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0