## NSN 5910-01-276-2267

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-276-2267 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 0.310 inches **Body Diameter:** Between 0.870 inches and 0.900 inches **Body Length:** Between 1.078 inches and 1.202 inches **Center To Center Distance Between Terminals Parallel To Diameter:** Between 0.285 inches and 0.315 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **End Application:** 5999-01-174-0693 processor, displ **Capacitance Value Per Section:** 1500.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 7.5 dc single section **Tolerance Range Per Section:** -10.00/+100.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Terminal Type And Quantity:** 3 uninsulated wire lead Shelf Life:

N/a

## NSN 5910-01-276-2267

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0