NSN 5910-01-276-2437

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-276-2437

Body Style:

Rotary

Terminal Length:

Between 0.126 inches and 0.184 inches

Overall Height:

0.177 inches

Overall Diameter:

0.216 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.196 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

0.196 inches

Quality Factor At 25 Deg Celsius:

500.0

Terminal Width:

Between 0.037 inches and 0.041 inches

End Application:

6625-01-251-4775 monitor communi

Inclosure Type:

Encased

Adjustment Device Torque:

Between 0.500 inch-ounces and 1.500 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+1.0/+3.0 single section

Nonderated Voltage Rating And Type:

63.0 dc continuous single section

Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius:

-4.50/+2.00 single section and -2.50/+2.00 single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

NSN 5910-01-276-2437

Ceramic Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0