

View Online at <https://aerobasegroup.com/nsn/5910-01-276-8070>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

1.000 inches

**Body Length:**

Between 0.195 inches and 0.220 inches

**Body Width:**

Between 0.220 inches and 0.290 inches

**Body Height:**

Between 0.075 inches and 0.110 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.155 inches and 0.205 inches

**Terminal Diameter:**

0.016 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

10.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

20.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.000

**Dc Leakage At Reference Temp:**

2.000 microamperes

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-49137 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-49137/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0