

View Online at https://aerobasegroup.com/nsn/5910-01-277-6053

Body Style: Plate-meshing Overall Length: 0.350 inches Terminal Length: 0.120 inches Overall Height: 0.270 inches Overall Width: 0.220 inches Overall Width: 0.220 inches Quality Factor At 25 Deg Celsius: 1000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.180 inches Inclosure Type: Uninclosed Insulation Dc Resistance At 25 Deg Celsius: 1000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Sheff Life: Na Unit Of Measure:  Demilitarization: No		
Overall Length:0.350 inchesTerminal Length:0.120 inchesOverall Height:0.270 inchesOuter and the set of the	Body Style:	
<ul> <li>O.350 inches</li> <li>Terminal Length:</li> <li>O.120 inches</li> <li>Overall Height:</li> <li>O.270 inches</li> <li>Overall Width:</li> <li>O.220 inches</li> <li>Overall Width:</li> <li>O.220 inches</li> <li>Quality Factor At 25 Deg Celsius:</li> <li>1000.0</li> <li>Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:</li> <li>O.180 inches</li> <li>Inclosure Type:</li> <li>Uninclosed</li> <li>Insulation De Resistance At 25 Deg Celsius:</li> <li>1000.0 megohms</li> <li>Mounting Facility Type And Quantity:</li> <li>2 terminal</li> <li>Nonderated Operating Temp:</li> <li>Between -40.0 degrees celsius and 70.0 degrees celsius</li> <li>Capacitance Range In Picofarads:</li> <li>+3.0/+27.0 single section</li> <li>Anderated Voltage Rating And Type:</li> <li>1 slotted screw</li> <li>Terminal Type And Quantity:</li> <li>2 printed circuit</li> <li>Sheff Life:</li> <li>N/a</li> <li>Insulation De Resistance At 25 Deg Celsius:</li> <li>Na</li> <li>Farminal Type And Quantity:</li> <li>Autor of Adage Rating And Type:</li> <li>Na</li> <li>Sheff Life:</li> <li>Na</li> <li>Farminal Type And Quantity:</li> <li>2 printed circuit</li> <li>Sheff Life:</li> <li>Na</li> <li>Farminal Type And Quantity:</li> <li>2 printed circuit</li> <li>Sheff Life:</li> <li>Na</li> <li>Fig:</li> </ul>	-	
Ireminal Length:         0.120 inches         Overall Height:         0.270 inches         Overall Width:         0.220 inches         Quality Factor At 25 Deg Celsius:         1000.0         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         0.180 inches         Inclosure Type:         Uninclosed         Insulation Dc Resistance At 25 Deg Celsius:         1000.0 megohms         Mounting Facility Type And Quantity:         2 terminal         Parter At 0.0 degrees celsius and 70.0 degrees celsius         Capacitance Range In Picofarads:         +3.0/+27.0 single section         Anderated Voltage Rating And Type:         15.0.0 de continuous single section         Anderated Serew         Istited screw         Istited screw         2 printed circuit         Sheft Life:         N/a         Int Of Measure:         -         -         Penillitarization:         No         Fig:	Overall Length:	
0.120 inches Verall Height: 0.270 inches 0.270 inches 0.220 inches 0.20	0.350 inches	
Overall Height:0.270 inchesOverall Width:0.220 inchesQuality Factor At 25 Deg Celsius:1000.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.180 inchesInclosure Type:UninclosedInsulation Dc Resistance At 25 Deg Celsius:1000.0 megohmsMounting Facility Type And Quantity:2 terminalPonderated Operating Temp:Between -40.0 degrees celsius and 70.0 degrees celsiusAnderated Voltage Rating And Type:150.0 dc continuous single sectionAdjustment Device Drive Type And Quantity:1 slotted screwFerminal Type And Quantity:1 slotted screwFerminal Type And Quantity:1 slotted screwMinch Device Drive Type And Quantity:1 slotted screwFerminal Type And Quantity:2 printed circuitNaDistil trie:NaFerminal Type And Quantity:NaPinited Type And Quantity:NaFig:NoFig:	Terminal Length:	
0.270 inches         Overall Width:         0.220 inches         Quality Factor At 25 Deg Celsius:         1000.0         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         0.180 inches         Inclosure Type:         Uninclosed         Insulation Dc Resistance At 25 Deg Celsius:         1000.0 megohms         Mounting Facility Type And Quantity:         2 terminal         Nonderated Operating Temp:         Between -40.0 degrees celsius and 70.0 degrees celsius         Capacitance Range In Picofarads:         +3.0/+27.0 single section         Adjustment Device Drive Type And Quantity:         1 slotted screw         Terminal Type And Quantity:         2 printed circuit         Sheff Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	0.120 inches	
Overall Width:         0.220 inches         Quality Factor At 25 Deg Celsius:         1000.0         Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:         0.180 inches         Inclosure Type:         Uninclosed         Insulation Dc Resistance At 25 Deg Celsius:         10000.0 megohms         Mounting Facility Type And Quantity:         2 terminal         Nonderated Operating Temp:         Between -40.0 degrees celsius and 70.0 degrees celsius         Capacitance Range In Picofarads:         +3.0/+27.0 single section         Nonderated Voltage Rating And Type:         150.0 dc continuous single section         Adjustment Device Drive Type And Quantity:         2 printed circuit         Shelf Life:         N/a         Unit Of Measure:               Demilitarization:         No         Fig:	Overall Height:	
0.220 inchesQuality Factor At 25 Deg Celsius:1000.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.180 inchesInclosure Type:UninclosedInsulation Dc Resistance At 25 Deg Celsius:10000.0 megohmsMounting Facility Type And Quantity:2 terminalPonderated Operating Temp:Between -40.0 degrees celsius and 70.0 degrees celsiusCapacitance Range In Picofarads:+3.0/+27.0 single sectionAndustret Voltage Rating And Type:150.0 de continuous single sectionAdjustment Device Drive Type And Quantity:1 slotted screwPerminal Type And Quantity:2 printed circuitMainMainDiff Desure:NaDiff Define:NaDiff Define:NaFreminal Type And Quantity:Pinted circuitFreminal Type And Quantity:NaDiff Define:NaFreminal Type And Quantity:Pinter CircuitFreminal Type And Quantity:Pinter CircuitFreminal Type And Quantity:NaDiff Define:NaPinter CircuitFreminal Type And Quantity:Pinter CircuitFreminal Type And Quantity:Pinter CircuitFreminal Type And Quantity:Pinter CircuitFreminal Type And Quantity:Pinter CircuitPinter CircuitPinter CircuitPinter Circuit<	0.270 inches	
Quality Factor At 25 Deg Celsius:1000.0Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.180 inchesInclosure Type:UninclosedInsulation Dc Resistance At 25 Deg Celsius:1000.0 megohmsMounting Facility Type And Quantity:2 terminalNonderated Operating Temp:Between -40.0 degrees celsius and 70.0 degrees celsiusCapacitance Range In Picofarads:+3.0/+27.0 single sectionMonderated Voltage Rating And Type:150.0 dc continuous single sectionAdjustment Device Drive Type And Quantity:2 stremial Type And Quantity:2 storted screwFerminal Type And Quantity:2 storted screwMonderated Notage Rating And Type:1 slotted screwMain ConcuitNaDeniltarization:Pined circuitFig:	Overall Width:	
1000.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.180 inches Inclosure Type: Uninclosed Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 2 printed circuit Shelf Life: N/a Unit of Measure: No Fig:	0.220 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:0.180 inchesInclosure Type:UninclosedInsulation Dc Resistance At 25 Deg Celsius:10000.0 megohmsMounting Facility Type And Quantity:2 terminalNonderated Operating Temp:Between -40.0 degrees celsius and 70.0 degrees celsiusCapacitance Range In Picofarads:+3.0/+27.0 single sectionMonderated Voltage Rating And Type:150.0 dc continuous single sectionAdjustment Device Drive Type And Quantity:1 slotted screwTerminal Type And Quantity:2 printed circuitShelf Life:N/aUnit Of Measure:-NoFig:	Quality Factor At 25 Deg Celsius:	
0.180 inches Inclosure Type: Uninclosed Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Monderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	1000.0	
Inclosure Type: Uninclosed Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Uninclosed Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Sheff Life: N/a Unit Of Measure:  Demilitarization: No	0.180 inches	
Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Sheff Life: N/a Init Of Measure:  Demilitarization: No	Inclosure Type:	
10000.0 megohms Mounting Facility Type And Quantity: 2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Uninclosed	
Mounting Facility Type And Quantity:         2 terminal         Nonderated Operating Temp:         Between -40.0 degrees celsius and 70.0 degrees celsius         Capacitance Range In Picofarads:         +3.0/+27.0 single section         Nonderated Voltage Rating And Type:         150.0 dc continuous single section         Adjustment Device Drive Type And Quantity:         1 slotted screw         Terminal Type And Quantity:         2 printed circuit         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:         No         Fig:	Insulation Dc Resistance At 25 Deg Celsius:	
2 terminal Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	10000.0 megohms	
Nonderated Operating Temp: Between -40.0 degrees celsius and 70.0 degrees celsius Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Mounting Facility Type And Quantity:	
Between -40.0 degrees celsius and 70.0 degrees celsius <b>Capacitance Range In Picofarads:</b> +3.0/+27.0 single section <b>Nonderated Voltage Rating And Type:</b> 150.0 dc continuous single section <b>Adjustment Device Drive Type And Quantity:</b> 1 slotted screw <b>Terminal Type And Quantity:</b> 2 printed circuit <b>Shelf Life:</b> N/a <b>Unit Of Measure:</b> - <b>Demilitarization:</b> No <b>Fiig:</b>	2 terminal	
Capacitance Range In Picofarads: +3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Nonderated Operating Temp:	
+3.0/+27.0 single section Nonderated Voltage Rating And Type: 150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Between -40.0 degrees celsius and 70.0 degrees celsius	
Nonderated Voltage Rating And Type:         150.0 dc continuous single section         Adjustment Device Drive Type And Quantity:         1 slotted screw         Terminal Type And Quantity:         2 printed circuit         Shelf Life:         N/a         Unit Of Measure:            No         Fig:	Capacitance Range In Picofarads:	
150.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	+3.0/+27.0 single section	
Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Nonderated Voltage Rating And Type:	
1 slotted screw Terminal Type And Quantity: 2 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	150.0 dc continuous single section	
Terminal Type And Quantity:   2 printed circuit   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Adjustment Device Drive Type And Quantity:	
2 printed circuit Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	1 slotted screw	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure:  Demilitarization: No Fiig:	2 printed circuit	
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
A096a0	Fiig:	
	A096a0	